

Lathe T460x1500

Ref: T460x1500



Technical specifications

MAX SWING OVER BED (MM)	410
MAX SWING OVER CARRIAGE (MM)	255
DISTANCE BETWEEN CENTERS (MM)	1500
SWING OVER RAM (MM)	580
RAM WIDTH (MM)	190
BED WIDTH (MM)	250
MAIN SPINDLE BORE (MM)	52
SPINDLE NOSE (MM)	CAMLOCK D1-6
SPINDLE MORSE TAPER	CM6
SPINDLE SPEED NUMBER AND RANGE (RPM)	(16) 25-1800
TAILSTOCK QUILL TAPER	CM4
METRIC PITCH (MM)	(39)0.2-14
WHITWORTH PITCH PER INCH	(45)2-72 TPI
MODULAR PITCH	(18)0.3-3.5
DIAMETRAL PITCH	(21)8-44 DP
LONGITUDINAL FEED NUMBER AND RANGE	(17)0.002-0.067
TRANSVERSAL FEED NUMBER AND RANGE	(17)0.001-0.0335
MAX CARRIAGE TRAVEL (MM)	210
MAX UPPER CARRIAGE TRAVEL (MM)	140
MAX TAILSTOCK QUILL TRAVEL (MM)	120
MAX TOOLS DIMENSIONS (MM)	25 x 25
MOTOR POWER (KW)	5.5 KW/7.4 CV
COOLING EQUIPMENT POWER (KW)	2,2 Kw/ 3 CV
VOLTAGE	380-400V/50Hz
DIMENSIONES (L X W X H) (MM)	2530x890x1620
WEIGHT (KG)	1550

Standard Equipment

- 3 Jaw Chuck Ø200 mm
- 4 Jaw Chuck Ø320 mm
- Dital 2 axis dro
- Face Chuck Ø350 mm
- 2 Axis Dro
- Reducing Sleeves MT6 to MT4
- Thread Dial Indicator
- Foot Brake
- Chip Collector Tray
- Carriage Stop
- Steady Rest
- Rear Splash Protection
- Coolant System
- 2 Dead Centers
- Levelling Pads
- Gear Exchange Set
- Tool Box
- Work Light
- CE Certificate