

Lathe T560x2000

Ref: T560x2000



Technical specifications

Centers height	280
Distance between column	3000
MAX SWING OVER BED (MM)	560
Swing Over Ram	785
MAX SWING OVER CARRIAGE (MM)	355
BED WIDTH (MM)	350
RAM WIDTH (MM)	170
MAIN SPINDLE BORE (MM)	80/105
SPINDLE NOSE (MM)	CAMLOCK D 1-8
MORSE TAPER OF MAIN SPINDLE	7 MT
SPINDLE SPEED RANGE (RPM)	25-2000
NUMBER OF SPEED	12
LONGITUDINAL FEED RANGE (MM/REV.)	0.059-1.646 mm/rev
TRANSVERSAL FEED RANGE (MM/REV.)	0.020-0.573 mm/rev
METRIC PITCH (MM)	0.2-14
WHITWORTH PITCH PER INCH	2-112 TPI
MODULAR PITCH	0.1-7 MP
DIAMETRAL PITCH	4-112 DP
MAX CARRIAGE TRAVEL (MM)	316
Max Upper Carriage Travel	130
DIAMETER OF TAILSTOCK QUILL	75
MAX TAILSTOCK QUILL TRAVEL (MM)	180
Max Tool Dimensions	25x25
MORSE TAPER OF TAILSTOCK	MT5
MOTOR POWER (KW)	7.5 Kw/10 CV
PUMP MOTOR POWER	0.1Kw/0.13 CV
VOLTAGE (V)	380-400 V / 50Hz
DIMENSIONS	4340 x 1150 x 1460
WEIGHT(KG)	2930

Standard Equipment

- 3-jaw chuck
- 4-jaw chuck
- Digital 2 axis dro.
- Face plate
- Steady rest
- Follow rest
- Drive plate
- Dead center
- Live center
- Splash guard
- Oil tray
- Thread dial indicator
- Lead screw protection
- Chuck protection
- Work lamp
- Coolant system
- Foot Brake
- Quick change tool post
- Tool holder protection
- Tools
- CE Certificate