

Lathe T410X1000

Ref: T410X1000



Technical specifications

MAX SWING OVER BED (MM)	410
MAX CARRIAGE TRAVEL (MM)	255
Distance between column	1000
Swing Over Ram	580
RAM WIDTH (MM)	190
SADDLE WIDE	250
MAIN SPINDLE BORE (MM)	52
SPINDLE TAPER	Camlock D1-6
SPINDLE MORSE TAPER	CM6
SPINDLE SPEED NUMBER AND RANGE (RPM)	(16) 25-1800
TAILSTOCK QUILL TAPER	CM4
METRIC PITCH (MM)	0.2-14
WHITWORTH PITCH PER INCH	2-72 TPI
MODULAR PITCH	0.3- 3.5
DIAMETRAL PITCH	8- 44 DP
LONGITUDINAL FEED NUMBER AND RANGE	0.05- 1.7
TRANSVERSAL FEED NUMBER AND RANGE	0.025-0.85
SADDLE STROKE	210
Max Upper Carriage Travel	140
MAX TAILSTOCK QUILL TRAVEL (MM)	120
MAX TOOLS DIMMENSIONS (MM)	20X20
MOTOR POWER (Kw/Hp)	2.2/3Kw- 3/4CV
COOLING EQUIPMENT POWER (KW)	0.1 Kw
VOLTAGE (V)	380-400 V / 50Hz
DIMENSIONS (MM)	2530x890x1620
WEIGHT(KG)	1160

Standard Equipment

- 2 axis XY display
- Ø200 plate
- Ø250 plate
- Ø350 plate
- Thread indicator
- Foot brake
- Chip tray
- Stop bar
- Fixed rear window
- Mobile rear window
- Rear splash guard
- Fixed points
- Leveling chocks
- Set service keys
- Work lamp
- Cooling system
- CE Certificate.

Images

