

Lathe T410VX1000

Ref: T410VX1000



Technical specifications

MAX SWING OVER BED (MM)	410
MAX CARRIAGE TRAVEL (MM)	205
Distance between column	1000
Swing Over Ram	580
RAM WIDTH (MM)	225
MAIN SPINDLE BORE (MM)	51
SPINDLE TAPER	Camlock D1-6
SPINDLE MORSE TAPER	MT3
SPINDLE SPEED NUMBER AND RANGE (RPM)	(2)30-2000/45-3000
TAILSTOCK QUILL TAPER	CM4
METRIC PITCH (MM)	0.4-7
WHITWORTH PITCH PER INCH	4-56 T.P.I
LONGITUDINAL FEED NUMBER AND RANGE	0.05-0.700
TRANSVERSAL FEED NUMBER AND RANGE	0.027-0.413
SADDLE STROKE	200
MAX TAILSTOCK QUILL TRAVEL (MM)	130
MAX TOOLS DIMMENSIONS (MM)	20X20
MOTOR POWER (Kw/Hp)	4KW/5,3CV
VOLTAGE (V)	380-400 V / 50Hz
DIMENSIONS (MM)	2114x994x1657
WEIGHT(KG)	900

Standard Equipment

- 2 axis XY display
- Ø200 plate
- Ø250 plate
- Ø350 plate
- Thread indicator
- Foot brake
- Chip tray
- Stop bar
- Fixed rear window
- Mobile rear window
- Rear splash guard
- Fixed points
- Leveling chocks
- Set service keys
- Work lamp
- Cooling system
- CE Certificate.

Images

